



SAR MAKINA

DOUBLE TWIST BUNCHING MACHINES





SBM 630 DOUBLE TWIST BUNCHING MACHINE

TECHNICAL SPECIFICATION

Maximum twist number	6500 twist/min
Maximum production speed	300 m/min
Cross section	0,10 - 6,00 mm ²
Lay Length	6-100 mm
Maximum Noise	80 dBA

REEL DIMENSIONS

Flange Diameter	630-560 mm
Traverse Width (max.)	400 mm
Barrel Diameter (min.)	280 mm

MOTORS

Bow	AC Motor
Spooler Motor	AC Servo Motor
Capstan Motor	AC Servo Motor
Traverse Motor	Step Motor

MACHINE DIMENSIONS

LxWxH	3000x1750x1700
Total Weight	approx. 3440 kg.

SBM 800 DOUBLE TWIST BUNCHING MACHINE

TECHNICAL SPECIFICATION

Maximum twist number	5000 twist/min
Maximum production speed	300 m/min
Cross section	0,25 - 16,00 mm ²
Lay Length	15-160 mm
Maximum Noise	80 dBA

REEL DIMENSIONS

Flange Diameter	800-630 mm
Traverse Width (max.)	500 mm
Barrel Diameter (min.)	315 mm

MOTORS

Bow	AC Motor
Spooler Motor	AC Servo Motor
Capstan Motor	AC Servo Motor
Traverse Motor	Step Motor

MACHINE DIMENSIONS

LxWxH	4000x2150x2200
Total Weight	approx. 6320 kg.



SBM 1250 DOUBLE TWIST BUNCHING MACHINE

TECHNICAL SPECIFICATION

Maximum twist number	1600 twist/min
Maximum production speed	240 m/min
Cross section	6 - 107,00 mm ²
Lay Length	30-300 mm
Maximum Noise	80 dBA

REEL DIMENSIONS

Flange Diameter	1250-800 mm
Traverse Width (max.)	800 mm
Barrel Diameter (min.)	400 mm

MOTORS

Bow	AC Motor
Spooler Motor	AC Servo Motor
Capstan Motor	AC Servo Motor
Traverse Motor	Step Motor

MACHINE DIMENSIONS

LxWxH	5850x3530x3940
Total Weight	approx. 11.300 kg.



SAR MAKİNA

Osmangazi Mh. Sanayi Cd. Kanuni Sk. No:12 PK. 41700 Darıca-Kocaeli-Türkiye
Tel: +90 262 653 90 82-PBX Fax: +90 262 653 90 89
marketing@sarmakina.com.tr - www.sarmakina.com.tr